



## C-U32/MFF

USB 3.2 GEN-2 Full Featured USB-C (M) to  
USB-C (M) Cable

| 4K/60 UHD (4:4:4)



C-U32/MFF is a USB-C(M) to USB-C(M), USB 3.2 Gen-2 SuperSpeed+ cable offering a whole new level of reliable connectivity thanks to Kramer's unique cable construction providing flexibility and our popular K-lock. Transfer Video 4K@60 4:4:4, data at incredible speeds (10G), high-rate charging (100W), – all with just one Passive cable.

C-U32/MFF offers throughput of up to 10Gbps when used with a USB 3.2 host and device. The symmetrical, low profile USB Type-C connector, with the integrated K-Lock mechanism, can be plugged in any direction, thus eliminating the frustration of getting the port insertion just right

## FEATURES

**Quality Construction** - Micro coax wires, triple shielding that helps prevent electromagnetic interference and ensures reliable data communication

**Reversible USB Type-C Connector** with integrated locking mechanism

**Video 4K@60 4:4:4 (DP Alt mode)**

**Transfer Rates** - Up to 10Gbps, USB 3.2 Gen 2

**USB 2.0**

**100W power (5A, 20V)**

**PC, Mac & Mobile Compatible**

**Plug and Play** - For monitors, Web cameras, printers, scanners, keyboards and other digital devices

**USB Backward Compatibility** - 1.0, 1.1, 2.0 and 3.0

**Logo on mold** as orientation mark

**RoHS REACH Compliant**



## TECHNICAL SPECIFICATIONS

---

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| OVERALL              | Type: USB 3.2 GEN-2                                                        |
|                      | Video 4K@60 4:4:4 (DP Alt Mode)                                            |
|                      | USB 3.2 Gen 2 10Gbps                                                       |
|                      | USB 2.0 480Mbps                                                            |
|                      | ETH Support: 10/100/1000 Mbps                                              |
| PHYSICAL             | Connector A: USB Type-C Male Nickel plated K-Lock connector with gold pins |
|                      | Connector A Length x Width x Height: 23x12x8mm                             |
|                      | Connector B: USB Type-C Male Nickel plated K-Lock connector with gold pins |
|                      | Connector B Length x Width x Height: 23x12x8mm                             |
| JACKET               | Material: PVC                                                              |
|                      | Color: Black                                                               |
|                      | Diameter 5.7 ±0.2mm                                                        |
|                      | Bending Radius: 34.2                                                       |
| ELECTRICAL           | Temperature Rating: 80°C                                                   |
|                      | Voltage Rating: 30V                                                        |
| STANDARDS COMPLIANCE | Safety: CE                                                                 |
|                      | Flammability Rating: VW-1                                                  |



## CONFIGURATIONS

|              |                                                                                                          |
|--------------|----------------------------------------------------------------------------------------------------------|
| C-U32/MFF-6  | USB 3.2 GEN-2 Full Featured USB-C (M) to USB-C (M) Flexible Passive Cable:<br>Cable Length 6ft (1.8m)    |
| C-U32/MFF-10 | USB 3.2 GEN-2 Full Featured USB-C (M) to USB-C (M) Flexible Passive Cable:<br>Cable Length 10ft (3m)     |
| C-U32/MFF-15 | USB 3.2 GEN-2 Full Featured USB-C (M) to USB-C (M) Flexible Passive Cable:<br>Cable Length — 15ft (4.6m) |