



## C-USB/C

USB 2.0 Type-C Cable

---



Kramer's C-USB/C cables connect USB-C enabled devices with standard USB-A, B and Micro B devices (laptops, hard drives, legacy printers, hubs, smartphones, tablets and cameras). C-USB/C cables offer a whole new level of connectivity to devices using the new USB Type-C connector. The symmetrical, low profile USB Type-C connector can be plugged in any direction, eliminating the frustration of getting the port insertion just right.

### FEATURES

---

**Quality Construction** - High-quality shielded twisted pair (STP) construction, helps to prevent electromagnetic interference and ensures reliable data communication

**Reversible USB Type-C Connector**

**Max. Data Rate** - 480Mbps

**Current Rating** - 3A and 5A

**PC, Mac & Mobile Compatible**

**Plug and Play** - For printers, scanners, keyboards and other digital devices

**Backward Compatibility** - USB specifications 1.0 and 1.1

**Molded Strain Relief** - On the USB A, B & Micro B ends

**RoHS Compliant**



## TECHNICAL SPECIFICATIONS

---

|                      |                                                   |
|----------------------|---------------------------------------------------|
| ELECTRICAL           | TYPE: USB 2.0                                     |
|                      | MAX. DATA RATE: 480Mbps                           |
|                      | POWER RATING: 100W max                            |
| PHYSICAL             | CONNECTOR A: USB Type-C male                      |
|                      | CONNECTOR B: C-USB/CC – USB Type-C male           |
|                      | C-USB/CB – USB Type-B male                        |
|                      | C-USB/CA – USB Type-A male                        |
|                      | C-USB/CMicroB – USB Type-Micro B male             |
|                      | CONNECTOR PLATING: Nickel                         |
|                      | CONDUCTORS: 28AWG                                 |
|                      | CABLE SHIELD TYPE: Aluminum-Mylar foil with braid |
| STANDARDS COMPLIANCE | OVERALL SHEATH DIAMETER: 4.0mm                    |
|                      | OUTER SHEATH COLOR: White                         |
|                      | REGULATORY: RoHS 2011/65/EU                       |
|                      |                                                   |



## CONFIGURATIONS

|                 |                                    |
|-----------------|------------------------------------|
| C-USB/CC-6      | USB 2.0 USB-C(M) to USB-C(M)       |
| C-USB/CC-10     | USB 2.0 USB-C(M) to USB-C(M)       |
| C-USB/CB-6      | USB 2.0 USB-C(M) to USB-B(M)       |
| C-USB/CB-10     | USB 2.0 USB-C(M) to USB-B(M)       |
| C-USB/CA-6      | USB 2.0 USB-C(M) to USB-A(M)       |
| C-USB/CA-10     | USB 2.0 USB-C(M) to USB-A(M)       |
| C-USB/CMicroB-3 | USB 2.0 USB-C(M) to USB Micro-B(M) |
| C-USB/CMicroB-6 | USB 2.0 USB-C(M) to USB Micro-B(M) |