



MA3-PS-4812

Modular Matrix PoE Power Supply



MA3-PS-4812 is a power supply for compatible modular matrices, enabling their PoE power delivery on compatible extension ports of matrix cards for remote powering of their connected devices, such as transmitters and receivers, to ease their installation

FEATURES

Easy to Install - Fits in a 1U space in a 19" rack above MTX3-34-M/VS-34FD



TECHNICAL SPECIFICATIONS

Power	Supply: 48V 12A Source: 100–240V AC 50/60Hz (receives power via MTX3–34–M/VS–34FD) Consumption: 5.2A
Environmental Conditions	Operating Temperature: 0° to +35°C (32° to 95°F) Storage Temperature: –20° to +60°C (–4° to 140°F) Humidity: 20% to 90%, RHL non–condensing
General	Size: 1U (H), 19" (W) Product Dimensions: 48.2cm x 13.8cm x 4.6cm (19" x 5.4" x 1.8") W, D, H Product Weight: 2.6kg (5.7lbs) approx Shipping Dimensions: 55cm x 27.7cm x 10.5cm (21.6" x 10.9" x 4.1") W, D, H Shipping Weight: 3.3kg (7.2lbs) approx
Product Dimensions	48.20cm x 13.80cm x 4.60cm (18.98" x 5.43" x 1.81") W, D, H
Product Weight	2.6kg (5.7lbs) approx
Shipping Dimensions	55.00cm x 27.70cm x 10.50cm (21.65" x 10.91" x 4.13") W, D, H
Shipping Weight	3.3kg (7.2lbs) approx